



Global Sublimation

Max. temperature: 200 °C
Max. material thickness: 30 mm
Electrical power: 380 V / three phase
Working height: 1000 mm

Product Information:

- › Designed for high quality sublimation
- › Working temperature ± 175 °C
- › Single sided anodized heating platen
- › Adjustable digital temperature control
- › Overheating protection
- › Average energy use 1 to 3 kW/h
- › Maintenance and oil free vacuum pumps
- › Vacuum suction points directly in platen
- › Custom sizes available



Code	Vacuum Pump	Heating Surface	Membrane		Max Pressing Height ¹
			Kind	Height	
G-SUB-1310-00	10 m ³ /h	130 x 100 cm	SR	0 mm	400 mm
G-SUB-2510-00	16 m ³ /h	250 x 100 cm	SR	0 mm	400 mm
G-SUB-3110-00	25 m ³ /h	310 x 100 cm	SR	0 mm	400 mm
G-SUB-3710-00	40 m ³ /h	370 x 100 cm	SR	0 mm	400 mm

Conditions for Global Sublimation

Delivery time: 4 Weeks on standard items, 6 weeks for custom sizes.
Shipping: Ex Works Moncada (Valencia) SPAIN.
Price: In Euros, exluded packaging, exluded VAT.
Warranty: 3 Years, except for the membrane.

Price and technical characteristics reserved to change without notice.