

GLOBAL Bench Top Press

PRODUCT INFORMATION

- Designed for individual and small productions
- Maintenance and oil free vacuum pump
- Max. vacuum pressure 9 t/m² (90%)
- 10 mm compact press board with 6 suction points
- Flat natural rubber membrane, 2 mm thick
- Available with silicone rubber membrane, 2 mm thick and heat resistant up to 230 °C (translucent)
- ▶ 220 Volt, single phase



Code	Vacuum Pump	Press Capacity	Membrane		Max Pressing
			Kind	Height	Height ¹
GBP-1006-NR00	No	100 x 60 cm	NR	0 mm	400 mm
GBP-1006-SR00	No	100 x 60 cm	SR	0 mm	400 mm
GBP-1006-NR00-08	8 m³/h	$100 \times 60 \text{ cm}$	NR	0 mm	400 mm
GBP-1006-SR00-08	8 m³/h	100 x 60 cm	SR	0 mm	400 mm

NR = Natural Rubber SR = Silicone Rubber

1 max. pressing height depends on the physical size of the component

Conditions for GLOBAL Bench Top Press

Delivery time: Normally on stock and can be shipped within short time.

Shipping: Ex Works Moncada (Valencia) SPAIN.
Price: In Euros, excluded packaging, excluded VAT.

Warranty: 2 Years, except for the membrane.

Price and technical characteristics reserved to change without notice.