



GLOBAL
VACUUM PRESSES
shaping the world

GLOBAL Ecotherm INDUSTRIAL

Double sided preheating oven

Max. temperature: 200 °C
Max. material thickness: 30 mm, adjustable
Electrical power: 380 V / three phase
Working height: 1000 mm

Product Information:

- ▶ Preheating oven for acrylic solid surface materials
- ▶ Working temperature ± 130 to 170 °C
- ▶ Pneumatic opening and closing system with foot pedals
- ▶ Adjustable digital temperature control
- ▶ Overheating protection
- ▶ Average energy use 1 to 3 kW/h
- ▶ Double sided heating platen
- ▶ Preheating time 1 min/mm material thickness



Code		Heating Surface
GET-I-1310-1Z		130 x 100 cm
GET-I-2510-1Z		250 x 100 cm
GET-I-2510-3Z	3 zones of	83 x 100 cm
GET-I-2514-1Z		250 x 140 cm
GET-I-2514-3Z	3 zones of	83 x 140 cm
GET-I-3110-1Z		310 x 100 cm
GET-I-3110-3Z	3 zones of	103 x 100 cm
GET-I-3114-1Z		310 x 140 cm
GET-I-3114-3Z	3 zones of	103 x 140 cm
GET-I-3710-1Z		370 x 100 cm
GET-I-3710-3Z	3 zones of	123 x 100 cm
GET-I-3714-1Z		370 x 140 cm
GET-I-3714-3Z	3 zones of	123 x 140 cm

Shipment for GLOBAL Ecotherm INDUSTRIAL

Delivery time: 4 Weeks on standard items, 6 weeks for custom sizes.
Shipping: Ex Works Moncada (Valencia) SPAIN.
Prize: In Euros, exluded packaging, excluded VAT.
Warranty: 3 Years.

Price and technical characteristics reserved to change without notice.