



GLOBAL Heating Bar

Electrical-heating bars

Remarkably heating bar constructed of an aluminium profile to withstand the rigours of daily use. GLOBAL electric heating bars are recommended for thermoforming solid surface material and thermoplastics. Each bar is equipped with a continuously adjustable thermostat to suit the particular application and is delivered with cover over the length for energy saving and occupational safety.

PRODUCT INFORMATION

- › Manufactured from thermomechanically resistant aluminium profiles
- › Anodised in silver, scratch and wear resistant
- › Continuously adjustable thermostat
- › Temperature control via countersunk bolt prevents operating errors
- › Cover for energy saving and homogeneous heat distribution included
- › Preheating time 2 minutes/mm material thickness (solid surfaces)
- › All sides usable
- › Plug & Play
- › Portable
- › 3m cable included

TECHNICAL DETAILS

- › Heat up time 5 - 10 min.
- › Max. operating temperature: 170 °C
- › Specific pressure load max. 16 kp/cm²
- › Cross section 64 x 46 mm
- › CEE European standard three pin plug
- › 220 Volt, single-phase



Code	Length	Electric Power
GHB-0600	60 cm	500 W
GHB-1100	110 cm	700 W
GHB-1600	160 cm	800 W
GHB-2100	210 cm	1100 W
GHB-2600	260 cm	1200 W
GHB-3100	310 cm	1450 W
GHB-3600	360 cm	1550 W
GHB-4100	410 cm	1700 W

Shipment for GLOBAL Heating Bars

Delivery time: 1 week, normally in stock.
Shipping: Ex Works Moncada (Valencia), SPAIN.
Prize: In Euros, packaging included, excluded VAT.
Warranty: 2 Years.

Price and technical characteristics reserved to change without notice.