

Specifications

Model	HT2512UV-Gen6	
Printhead	2 - 8 Ricoh Gen6	
Resolution	600 x 1800 DPI	
Capacity	Draft Mode	60 m ² /h
	Production Mode	45 m ² /h
	Quality Mode	31 m ² /h
Max. Print Width	2.5 x 1.22 m	
Material Thickness	100 mm	
Applications	A wide variety of application in terms of acrylic, PVC, wood, glass, ceramic tile etc.	
Ink	eco-friendly UV curing ink (VOC free)	
Color	C, M, Y, K, Lc, Lm, V, W	
Dimension (L x W x H)	4.67 x 2.51 x 1.38 m	
Net Weight	1150 Kg	
Gross Weight	1745 Kg	
Power Supply	400VAC.50Hz 3P/N/PE; UV LED light 230VAC.50Hz L/N/PE	
Power Consumption	7KW (18A) , LED light 2.5KW (11A)	
RIP Software	Caldera	
UV Curing System	LED	
Interface	Hi-Speed PCIE	
Operating Environment	Temperature: 18°C~30°C (64°F~86°F)	
	Relative Humidity: 30%~70% (non-condensing)	

HandTOP
汉拓数码



HT2512UV-Gen6

- World-Class industrial design & excellent image data processing technology
- Wide variety of applications in broad field including brand lightbox advertisement in subway, airport & shopping mall and ceiling soft film project
- A top-level R&D team with 20 years of industry experience & 37 patents
- Obtained ISO:9001 International Quality System Certification & EU CE Certification
- Worldwide customer support , 24 x 7 technical support and service

Shenzhen HANDTOP Tech Co.,Ltd



Add:The Third Factory, NO.322 Yuanhu Road, Longgang District Shenzhen China.
Tel: +86 0755-2796 0460
Fax: +86 0755-2321 7841
E-mail: info-handtop@hanglorygroup.com
http://www.handtopuv.com



©Above information for reference only and subject to change without notice. Shenzhen Handtop Tech Co.,Ltd all rights reserved.

—
-“You want to produce stunning & beautiful things to delight your customers?”
-“So do we!”



2512UV—Gen6

01 Strong Guideway - Rail & Frame Structure

Square steel welding, annealing, more stable and stronger.

02 Ricoh Gen6 Printhead Inkjet Technology

Variable ignition frequency reaches 35KHZ, higher printing speed, productivity increased by more than 50%; ink drop size reduced from 7PL to 5PL, smaller ink drops deliver higher printing quality.

03 Water-Cooling LED Curing System

An excellent curing function with low irradiation temperature and eco-friendly water-cooling LED system.

04 Automatic Negative Pressure System

Negative pressure controlled automatically.
Set the negative pressure data from software which is more stable.
Extend the lifetime of negative pressure pump.

05 Automatic Height Adjustment System

Automatically detects the height of media up to 100 mm thickness and calibrates printhead distance for variable dot.

06 Controllable Suction Area

Four independent suction areas controlled by different handles.

07 Dual Guideway-Rail Design

Carriage moves smoothly with precise dual guideway-rail.



Wide Color Gamut

Support optional color mode according to different application.




RIP Software

08 Y-Direction Lead-Screw System

More accurate Y-direction positioning controlled by the independent servo motor.

09 X-Direction High-Quality Motor Control System

Equipped with high-quality motor, guarantee stable operation.



Greyscale Inkjet Technology

Greyscale printing not only save the cost of ink ; but also make the image more delicate, the color brighter. Thus it improves the performance of the pictures and make them more impressive.